



NOTES:

1. SUBSTRATE:
N-BK7
2. S2 TO BE PARALLEL WITH S1 TO <1 ARCMIN
3. COATING (APPLY ACROSS CLEAR APERTURE)
S1 & S2: $R(\text{AVG}) \leq 1.75\% @ 400 - 700\text{nm}$

4. FINE GRIND SURFACE

5. RoHS COMPLIANT
6. SURFACE FLATNESS (P-V):
 $\lambda/4$ (per inch over clear aperture)



**FOR INFORMATION ONLY:
DO NOT MANUFACTURE
PARTS TO THIS DRAWING**

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE
DIMENSIONS ARE FOR REFERENCE ONLY

	S1	S2
SHAPE	PLANO	PLANO
SURFACE QUALITY	60-40	60-40
CLEAR APERTURE	Ø67.50	Ø67.50
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED

THIRD ANGLE PROJECTION	TITLE	Edmund Optics®	
		75mm DIA., 4mm THICK, MgF2 COATED $\lambda/4$ N-BK7 WINDOW	
ALL DIMS IN	mm	DWG NO	62608
			SHEET 1 OF 1