




NOTES:

1. SUBSTRATE MATERIAL:
N-BK7
2. COATING (APPLY ACROSS CLEAR APERTURE)

S1 & S2: MgF2




R(avg) ≤1.75% @ 400 - 700nm

3. FINE GROUND SURFACE
4. POWER, IRREGULARITY, AND SURFACE QUALITY
SPECIFICAIONS APPLY ACROSS CLEAR APERTURE
5. RoHS COMPLIANT



**FOR INFORMATION ONLY:
DO NOT MANUFACTURE
PARTS TO THIS DRAWING**

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE
DIMENSIONS ARE FOR REFERENCE ONLY

REV. A	S1	S2	 Edmund Optics®						
SHAPE	CONVEX	PLANO						EFL	15
RADIUS	7.75	∞	BFL	13.22					
SURFACE QUALITY	60-40	60-40							
CLEAR APERTURE	9.00 X 19.00	9.00 X 19.00			TITLE	10mm H X 20mm L X 15mm FL MgF2 COATED, CYLINDER LENS			
COATING APERTURE	9.00 X 19.00	9.00 X 19.00							
BEVEL	PROTECTED AS NEEDED	PROTECTED AS NEEDED	ALL DIMS IN	mm	DWG NO	47773	SHEET 1 OF 1		