
NOTES:


- 1. SUBSTRATE: ZnSe
- 2. SURFACE \$2 TO BE PARALLEL TO SURFACE \$1 TO WITHIN < 3 ARCMIN
- 3. COATING (APPLY ACROSS COATING APERTURE)

S1& S2: NONE

4. FINE GRIND SURFACE

5. RoHS: COMPLIANT






FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

	\$1	\$2		
SHAPE	PLANO	PLANO		
SURFACE QUALITY	40-20	40-20		1
SURFACE FLATNESS @ 10.6µm	λ/20	λ/20	THIRD ANGLE PROJECTION	+
CLEAR APERTURE	Ø22.50	Ø22.50		<u>'</u>
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED	ALL DIMS IN	n

			Edmund Optic	;S
IRD ANGLE	$\phi \Leftrightarrow$	TITLE	25mm DIA x 5mm THICK UNCOATED Zn WINDOW	Se
LL DIMS IN	mm	DWG NO	39393	SH 1



SHEET

1 OF 1