

## NOTES:

- 1. SUBSTRATE: Fused Silica
- 2. SURFACE S2 TO BE PARALLEL TO SURFACE S1 TO WITHIN < 3 ARCMIN
- 3. COATING (APPLY ACROSS COATING APERTURE)

S1& S2: NONE

4. FINE GRIND SURFACE





## FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

	\$1	\$2		P	Edmund Optic	C®
SHAPE	PLANO	PLANO				,S
SURFACE ACCURACY P-V AT 632.8nm	0.10 WAVE	0.10 WAVE			50.8 Dia x 6.35 FS Laser Window Unc	·td
SURFACE QUALITY	10-5	10-5	THIRD ANGLE PROJECTION	TITLE	30.0 Did x 0.33 13 Edser Willdow one	.iu
CLEAR APERTURE	Ø45.72	Ø45.72				CLIEFT
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED	ALL DIMS IN mm	DWG NO	37690	SHEET 1 OF 1