

## NOTES:

- 1. SUBSTRATE: N-BK7
- 2. S2 TO BE PARALLEL WITH S1 TO < 1 ARCMIN
- 3. COATING (APPLY ACROSS CLEAR APERTURE) \$1 & \$2: R(ABS) <0.25% @ 532nm R(ABS) <0.25% @ 1064nm R(AVG) <1.0% @ 500 - 1100nm



- 5. Rohs Compliant
- 6. SURFACE FLATNESS (P-V): λ/4 (per inch over clear aperture)





## FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

	\$1	\$2
SHAPE	PLANO	PLANO
SURFACE QUALITY	60-40	60-40
CLEAR APERTURE	Ø45.00	Ø45.00
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED

				Edmund Optics®		
	THIRD ANGLE _ PROJECTION		TITLE	50mm DIA., 3mm THICK, YAG-BBAR COATED, λ/4 N-BK7 WINDOW		
_	ALL DIMS IN	mm	DWG NO	13326	SHEET 1 OF	

