NOTES:

1. SUBSTRATE:


HOYA GLASS: ND-0.3


2. SURFACE S2 TO BE PARALLEL WITH SURFACE S1 TO WITHIN < 0.02mm


FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING



- 4. COATING SPECIFICATION: \$1 & \$2:R(AVG) ≤0.4% @ 425 - 675nm
- 5. OPTICAL DENSITY: 3 +/-0.3 @ 400-700nm
- 6. TRANSMISSION (%): 0.1% AVERAGE FROM 400-700nm
- 7. ROHS COMPLIANT







SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY



| | S1 | S2 | | TITLE | 3.0 OD, 50mm DIA., VIS 0° COATED, ABSORPTIVE ND FILTER | | |
|-----------------|----------------------|----------------------|------------------------|-------|--|------------------|-----------------|
| SHAPE | PLANO | PLANO | THIRD ANGLE PROJECTION | | | | |
| SURFACE QUALITY | 80-50 | 80-50 | | 1 | | 7.555.11.11.2.12 | OUEET |
| BEVEL | PROTECTIVE AS NEEDED | PROTECTIVE AS NEEDED | ALL DIMS IN | mm | DWG NO | 13126 | SHEET 1 OF 1 |