NOTES:

1. SUBSTRATE: Fused Silica (Corning 7980)

2. ROHS: COMPLIANT

3. SURFACE S2 TO BE PARALLEL TO SURFACE S1 TO WITHIN <5 ARCMIN


4. COATING (APPLY ACROSS CLEAR APERTURE)


S1&S2: NONE


5. TRANSMITTED WAVEFRONT DISTORTION: ≤ 1λ



FINE GRIND SURFACE







FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

		\$1	\$2	
	SHAPE	PLANO	PLANO	
	SURFACE QUALITY	60-40	60-40	
	CLEAR APERTURE	Ø 45.00	Ø 45.00	
	BEVEL	PROTECTED AS NEEDED	PROTECTED AS NEEDED	
_			-	

		•
	1	
THIRD ANGLE PROJECTION		
	<u> </u>	
ALL DIMS IN	mm	

	Edmund Optics®
TITI F	50mm Dia. 2mm Thick Uncoated, 1λ Fused
IIILE	Silica Window

L DIMS IN mm DWG NO 19842 SHEET 1 OF 1