

## Solid State UV Flood Light Systems



Solid State UV Flood Light Systems

Produkt #16-762 **2 In Stock**

- 1 + €3.135<sup>00</sup>

**+ WARENKORB**

Mengenrabatte	
Stk. 1+	€3.135,00 stückpreis
Need More?	<a href="#">Angebotsanfrage</a>

**i** Preise exklusiv der geltenden Mehrwertsteuer und Abgaben

Downloadbereich

### Produktdetails

**Lebensdauer (Stunden):**  
>20,000

### Physikalische und mechanische Eigenschaften

**Größe (mm):**  
UV Curing Head: 55 x 52 x 148  
Control Box: 160 x 150 x 80

### Optische Eigenschaften

**Wellenlänge (nm):**

380.00 ±5

**Beam Size (mm):**

50 x 50mm (30mm WD)  
100 x 100mm (100mm WD)

**Arbeitsabstand (mm):**

30 - 100

**Bestrahlungsstärke (W/cm<sup>2</sup>):**

0.8

## Anschlussmöglichkeiten Hardware & Schnittstelle

**Spannungsversorgung:**

AC 100 - 240V

## Konformität mit Standards

**Konformitätszertifikat:**

[Anzeigen](#)

## Produktdetails

- Large, Uniform UV Light Output
- 380nm Center Wavelength
- Up to 0.8W/cm<sup>2</sup> UV Irradiance

Solid State UV Flood Light Systems produce a large, uniform output beam of UV light centered at 380nm. These systems consist of a controller box with a built-in timer for automated curing and a handheld UV flood light with an on-off switch. The controller box features integrated heat sinks and a cooling fan, allowing for continuous operation without a change in UV intensity. Solid State UV Flood Light Systems are ideal for UV curing applications, especially those with either large components or multiple small components to cure.