

Solid State UV Flood Light Systems (Recertified 05-P)



Solid State UV Flood Light Systems

Produkt #16-762-RCD-05P REZERTIFIZIERT **1 In Stock**

⊖ 1 ⊕ €2.250⁰⁰

+ WARENKORB

Mengenrabatte	
Stk. 1+	€2.250,00 stückpreis
Need More?	Angebotsanfrage

ⓘ Preise exklusiv der geltenden Mehrwertsteuer und Abgaben

Downloadbereich

Produktdetails

Lebensdauer (Stunden):
>20,000

Physikalische und mechanische Eigenschaften

Größe (mm):
UV Curing Head: 55 x 52 x 148
Control Box: 160 x 150 x 80

Optische Eigenschaften

Wellenlänge (nm):

380.00 ±5

Beam Size (mm):

50 x 50mm (30mm WD)
100 x 100mm (100mm WD)

Arbeitsabstand (mm):

30 - 100

Bestrahlungsstärke (W/cm²):

0.8

Anschlussmöglichkeiten Hardware & Schnittstelle

Spannungsversorgung:

AC 100 - 240V

Konformität mit Standards

Konformitätszertifikat:

[Anzeigen](#)

Produktdetails

- Large, Uniform UV Light Output
- 380nm Center Wavelength
- Up to 0.8W/cm² UV Irradiance

Solid State UV Flood Light Systems produce a large, uniform output beam of UV light centered at 380nm. These systems consist of a controller box with a built-in timer for automated curing and a handheld UV flood light with an on-off switch. The controller box features integrated heat sinks and a cooling fan, allowing for continuous operation without a change in UV intensity. Solid State UV Flood Light Systems are ideal for UV curing applications, especially those with either large components or multiple small components to cure.